



## Savita Oil Technologies Limited

Plot No. 10/2, Kharadpada, P.O. Naroli, Silvassa 396 230 U.T.D. & NH  
Tel :+91-7574843505, 7574843521-22; www.savita.com

SAVSOL | TRANSOL

### TECHNICAL DATA SHEET

**Product Name** : SAV SUPERIOR 505 PLUS

SR. NO.	CHARACTERISTICS	TEST METHOD	TYPICAL VALUES
1	APPEARANCE	VISUAL	CLEAR & BRIGHT
2	COLOUR	ASTM D-1500	L 1.0
3	DENSITY AT 29.5 <sup>o</sup> C, g/cc	ASTM D-1298	0.8640
4	K.VISCOSITY AT 40 <sup>o</sup> C, cst	ASTM D-445	94.92
5	K.VISCOSITY AT 100 <sup>o</sup> C, cst	ASTM D-445	11.17
6	VISCOSITY INDEX	ASTM D-2270	104
7	POUR POINT, <sup>o</sup> C	ASTM D- 97	-12
8	FLASH POINT, <sup>o</sup> C	ASTM D-92	240
9	TOTAL ACID No,mgKOH/g	ASTM D-664	0.03
10	WATER CONTENT, ppm	ASTM D-6304	50

PREPARED BY: Harshal

AUTHORISED SIGNATURE