

SAVOFILL SP - 100

Product Description: Savofil SP 100 is a Technical Wax based on Petroleum jelly for Industrial purpose. It is mainly used as a flooding compound for cables.

As this product enhances insulation characteristics, relative wide temperature working range, excellent oxidation stability and thermal insulation characteristics it improves shelf life of such cables .it could be used also for other Industrial metal protection.

CHARACTERISTICS

Sr.no.	Parameters	Test method	Specification	Typical value
1	Drop Point, °C	ASTM D - 566	100±5	102
2	C. Penetration @ 25°C, dmm	ASTM D - 937	20 - 50	40
3	Fluency and separation (50°C,24Hrs.)	IEC - 811-1	Pass	Pass
4	Dielectric constant @ 23°C	ASTM D - 150	< 2.3	2.15
5	Volume resistivity @23 °C	ASTM D - 150	>1E+14	5.4X10 ¹⁴
6	Aging/Corrosion	EN 50326(6.12.2)	Pass	Pass
7	Colour	ATM D - 1500	To report	< 1.0
8	Acid value	ASTM D 974	<0.5	0.054
9	Flash Point °C	ASTM D 92	>280	>280

AVAILABLE PACKING

1. 170 Kg MS open top drums.
2. 27 kg carton (slabs)

STORAGE CONDITIONS

Store in dry, ventilated, and ambient temperature. Keep away from the source of heat/sunlight. Keep tightly closed when not in use.

SAVITA OIL TECHNOLOGIES LTD

Reg office address: 66/67, 6th floor, Nariman Bhavan, Nariman Point, Mumbai, INDIA. Pin 400021.

Contact: Tel: +91-22-22883061, 66246200;

E mail: (Other than India) ibdexports@savita.com;

E.mail (India) splsalesadmin@savita.com website: www.savita.com

An ISO 9001:2015, ISO 14001:2015 & ISO 45001:2018 certified company.